


## Schottky Barrier Rectifier

High Barrier Technology for Improved High Temperature Performance



### FEATURES

- Guardring for overvoltage protection
- Lower power losses, high efficiency
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- High frequency operation
- Meets MSL level 1, per J-STD-020, LF maximum peak of 245 °C (for TO-263AB package)
- Solder dip 260 °C, 40 s (for TO-220AC and ITO-220AC package)
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

For use in low voltage, high frequency rectifier of switching mode power supplies, freewheeling diodes, dc-to-dc converters or polarity protection application.

### PRIMARY CHARACTERISTICS

$I_{F(AV)}$	7.5 A
$V_{RRM}$	35 V to 60 V
$I_{FSM}$	150 A
$V_F$	0.55 V, 0.61 V
$I_R$	50 $\mu$ A
$T_J \text{ max.}$	175 °C

### MECHANICAL DATA

**Case:** TO-220AC, ITO-220AC, TO-263AB

Epoxy meets UL 94V-0 flammability rating

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

**Polarity:** As marked

**Mounting Torque:** 10 in-lbs maximum

### MAXIMUM RATINGS ( $T_C = 25$ °C unless otherwise noted)

PARAMETER	SYMBOL	MBR7H35	MBR7H45	MBR7H50	MBR7H60	UNIT
Maximum repetitive peak reverse voltage	$V_{RRM}$	35	45	50	60	V
Working peak reverse voltage	$V_{RWM}$	35	45	50	60	V
Maximum DC blocking voltage	$V_{DC}$	35	45	50	60	V
Max. average forward rectified current (Fig. 1)	$I_{F(AV)}$	7.5				A
Non-repetitive avalanche energy at 25 °C, $I_{AS} = 4$ A, $L = 10$ mH	$E_{AS}$	80				mJ
Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load	$I_{FSM}$	150				A
Peak repetitive reverse surge current at $t_p = 2.0$ $\mu$ s, 1 kHz	$I_{RRM}$	1.0		0.5		A
Peak non-repetitive reverse energy (8/20 $\mu$ s waveform)	$E_{RSM}$	20		10		mJ
Electrostatic discharge capacitor voltage human body model: $C = 100$ pF, $R = 1.5$ k $\Omega$	$V_C$	25				kV
Voltage rate of change (rated $V_R$ )	dV/dt	10 000				V/ $\mu$ s

**MAXIMUM RATINGS** ( $T_C = 25\text{ }^\circ\text{C}$  unless otherwise noted)

PARAMETER	SYMBOL	MBR7H35	MBR7H45	MBR7H50	MBR7H60	UNIT
Operating junction and storage temperature range	$T_J, T_{STG}$	- 65 to + 175				$^\circ\text{C}$
Isolation voltage (ITO-220AC only) from terminal to heatsink $t = 1$ min	$V_{AC}$	1500				V

**ELECTRICAL CHARACTERISTICS** ( $T_C = 25\text{ }^\circ\text{C}$  unless otherwise noted)

PARAMETER	TEST CONDITIONS	SYMBOL	MBR7H35 MBR7H45		MBR7H50 MBR7H60		UNIT
			TYP.	MAX.	TYP.	MAX.	
Maximum instantaneous forward voltage <sup>(1)</sup>	$I_F = 7.5\text{ A}$	$V_F$	-	0.63	-	0.73	V
	$I_F = 7.5\text{ A}$		0.50	0.55	0.58	0.61	
	$I_F = 15\text{ A}$		-	0.75	-	0.87	
	$I_F = 15\text{ A}$		0.61	0.66	0.68	0.72	
Maximum reverse current at rated $V_R$ <sup>(2)</sup>	$T_C = 25\text{ }^\circ\text{C}$	$I_R$	-	50	-	50	$\mu\text{A}$ mA
	$T_C = 125\text{ }^\circ\text{C}$		3.0	10	2.0	10	

**Notes:**(1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle(2) Pulse test: Pulse width  $\leq 40$  ms**THERMAL CHARACTERISTICS** ( $T_C = 25\text{ }^\circ\text{C}$  unless otherwise noted)

PARAMETER	SYMBOL	MBR	MBRF	MBRB	UNIT
Thermal resistance, junction to case	$R_{\theta JC}$	3.0	5.0	3.0	$^\circ\text{C/W}$

**ORDERING INFORMATION** (Example)

PACKAGE	PREFERRED P/N	UNIT WEIGHT (g)	PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
TO-220AC	MBR7H45-E3/45	1.80	45	50/tube	Tube
ITO-220AC	MBRF7H45-E3/45	1.94	45	50/tube	Tube
TO-263AB	MBRB7H45-E3/45	1.33	45	50/tube	Tube
TO-263AB	MBRB7H45-E3/81	1.33	81	800/reel	Tape and reel
TO-220AC	MBR7H45HE3/45 <sup>(1)</sup>	1.80	45	50/tube	Tube
ITO-220AC	MBRF7H45HE3/45 <sup>(1)</sup>	1.94	45	50/tube	Tube
TO-263AB	MBRB7H45HE3/45 <sup>(1)</sup>	1.33	45	50/tube	Tube
TO-263AB	MBRB7H45HE3/81 <sup>(1)</sup>	1.33	81	800/reel	Tape and reel

**Note:**

(1) Automotive grade AEC Q101 qualified



**RATINGS AND CHARACTERISTICS CURVES**

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 4. Typical Reverse Characteristics Per Leg




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current Per Leg




Figure 5. Typical Junction Capacitance Per Leg




Figure 3. Typical Instantaneous Forward Characteristics Per Leg




Figure 6. Typical Transient Thermal Impedance Per Leg


# MBR(F,B)7H35 thru MBR(F,B)7H60

New Product

Vishay General Semiconductor



## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**